

MTD6 series driver accept all standard 1/4" Dr. bit adapters or 1/4" Dr. sockets.

1/4" Dr. Male

MTD6 series, with two windows of scale reading, offering accurate torque setting.

## MTD6 Torque Screwdriver Adjustable Torque

ITEM NO.	Driver	Range	Nm / in.lb	Ø m/m	L mm	g	Packing
MTD6-1402N	1/4"	0.4-2 Nm / 4-20 in.lb	0.05 / 0.1	24.8	134	128	30 pcs/CTN
MTD6-1405N	1/4"	1-5 Nm / 10-50 in.lb	0.1 / 1	33.8	160	128	30 pcs/CTN
MTD6-1408N	1/4"	2-8 Nm / 10-80 in.lb	0.1 / 1	33.8	160	282	30 pcs/CTN
MTD6-1410N	1/4"	2-10 Nm / 20-100 in.lb	0.1 / 1	33.8	160	300	30 pcs/CTN

MTD6-NS series driver accept all standard 6.35mm hex screwdriver bits.

6.35mm female hex

MTD6-NS series, with two windows of scale reading, offering accurate torque setting.

## MTD6-NS Torque Screwdriver Adjustable Torque

ITEM NO.	Driver	Range	Nm	Ø m/m	L mm	g	Packing
MTD6-1402NS	6.35mm	0.4-2 Nm	0.05	24.8	134	128	30 pcs/CTN
MTD6-1405NS	6.35mm	1-5 Nm	0.1	33.8	160	128	30 pcs/CTN
MTD6-1408NS	6.35mm	2-8 Nm	0.1	33.8	160	282	30 pcs/CTN
MTD6-1410NS	6.35mm	2-10 Nm	0.1	33.8	160	300	30 pcs/CTN

MOT6 & MOT6-NS series, with Sliding T-Handle use more convenient.