



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

SQUARE HANDLE



•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060040	1/2"	34-340	25-250.9	301-3010	770mm	2Kgs	45 teeth, 8 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060039	3/8"	20-200	14.8-147	178-1780	570mm	1.6Kgs	45 teeth, 8 action
DG[®]-II 11060042	1/2"	20-200	14.8-147	178-1780	570mm	1.6Kgs	45 teeth, 8 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060038	3/8"	10-135	7.4-99.6	89-1198	400mm	1.2Kgs	45 teeth, 8 action
DG[®]-II 11060041	1/2"	10-135	7.4-99.6	89-1198	400mm	1.2Kgs	45 teeth, 8 action

•Flexible Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060049	3/8"	20-200	14.8-147	178-1780	570mm	1.6Kgs	48 teeth, 7.5 action
DG[®]-II 11060051	1/2"	20-200	14.8-147	178-1780	570mm	1.6Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060043	3/8"	10-135	7.4-99.6	89-1198	400mm	1.05Kgs	48 teeth, 7.5 action
DG[®]-II 11060050	1/2"	10-135	7.4-99.6	89-1198	400mm	1.05Kgs	48 teeth, 7.5 action



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

ROUND HANDLE



•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060064	1/2"	34-340	25-250.9	301-3010	769mm	1.7Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060061	3/8"	20-200	14.8-147	178-1780	569mm	1.35Kgs	48 teeth, 7.5 action
DG[®]-II 11060063	1/2"	20-200	14.8-147	178-1780	569mm	1.35Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060060	3/8"	10-135	7.4-99.6	89-1195	394mm	1.05Kgs	48 teeth, 7.5 action
DG[®]-II 11060062	1/2"	10-135	7.4-99.6	89-1195	394mm	1.05Kgs	48 teeth, 7.5 action

•Flexible Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060066	3/8"	20-200	14.8-147	178-1780	576mm	1.35Kgs	48 teeth, 7.5 action
DG[®]-II 11060068	1/2"	20-200	14.8-147	178-1780	576mm	1.35Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060065	3/8"	10-135	7.4-99.6	89-1195	401mm	1.05Kgs	48 teeth, 7.5 action
DG[®]-II 11060067	1/2"	10-135	7.4-99.6	89-1195	401mm	1.05Kgs	48 teeth, 7.5 action



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

• Ø16mm Spigot Interchangeable Head

- Special designed sensor and super CPU measure and calculate the torque applied and the value is shown on LCD screen.
- Interchangeable designs helps the user to change accessories for different using.
- Ø16mm spigot is designed for professional market, and can fit with other Ø16mm spigot accessories.
- ER accessories can be used in CNC machines for fastening or loosening lathe tools.
- Open ended head, ring heads, and ratchet heads are available.



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060290	Ø16mm	34-340	25-250.9	301-3010	769mm	1.4Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060116	Ø16mm	20-200	14.8-147	178-1780	540mm	1.1Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060115	Ø16mm	10-135	7.4-99.6	89-1195	365mm	0.8Kgs

• 9X12mm / 14X18mm Female Interchangeable Head

- Special designed sensor and super CPU measure and calculate the torque applied and the value is shown on LCD screen.
- Interchangeable designs helps the user to change accessories for different using.
- Standard 9X12MM and 14X18MM inserting size can fit all 9X12MM or 14X18MM inserting accessories.
- Ratchet heads, open ended heads, ring heads, open ring heads, and adjustable spanner heads can be chosen for different purposes.



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060292	14X18mm	34-340	25-250.9	301-3010	742mm	1.5Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060118	9X12mm	20-200	14.8-147	178-1780	540mm	1.1Kgs
DG-II 11060291	14X18mm	20-200	14.8-147	178-1780	540mm	1.15Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060117	9X12mm	10-135	7.4-99.6	89-1195	365mm	0.8Kgs



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

ANGLE MEASURING HEAD

- Special designed sensor and super CPU measure and calculate the torque applied and the value is shown on LCD screen.
- Combine angle gauge with digital torque wrench, and offer the angle and torque measuring at the same time.
- Obvious scales of the angle gauge avoid any misreadings.
- Rotate the angle plate to zero, and fasten the screw to desired or required angle. The arrow on the plate indicates the degree the user occurred.



P.A.T

•Fixed



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060110	1/2"	34-340	25-250.9	301-3010	769mm	1.63Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060107	3/8"	20-200	14.8-147	178-1780	569mm	1.28Kgs	48 teeth, 7.5 action
DG®-II 11060109	1/2"	20-200	14.8-147	178-1780	569mm	1.28Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060106	3/8"	10-135	7.4-99.6	89-1195	394mm	1Kgs	48 teeth, 7.5 action
DG®-II 11060108	1/2"	10-135	7.4-99.6	89-1195	394mm	1Kgs	48 teeth, 7.5 action

•Flexible



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060112	3/8"	20-200	14.8-147	178-1780	576mm	1.28Kgs	48 teeth, 7.5 action
DG®-II 11060114	1/2"	20-200	14.8-147	178-1780	576mm	1.28Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060111	3/8"	10-135	7.4-99.6	89-1195	401mm	1Kgs	48 teeth, 7.5 action
DG®-II 11060113	1/2"	10-135	7.4-99.6	89-1195	401mm	1Kgs	48 teeth, 7.5 action



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

INDUSTRIAL HANDLE



•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG®-II 11060119	3/4"	60-600	44-443	531-5310	1248mm	5.94Kgs	24 teeth, 15 action
DG®-II 11060120	3/4"	80-800	59-590	708-7080	1248mm	5.94Kgs	24 teeth, 15 action
DG®-II 11060121	3/4"	100-1000	74-738	885-8851	1248mm	5.94Kgs	24 teeth, 15 action
DG®-II 11060185	1"	150-1500	110.6-1106	1328-13276	1248mm	5.94Kgs	24 teeth, 15 action
DG®-II 11060341	1"	200-2000	147-1470	1780-17800	2000mm	12Kgs	24 teeth, 15 action

•Ø22mm Spigot Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG®-II 11060286	Ø22mm	60-600	44-443	531-5310	1188mm	5.6Kgs
DG®-II 11060287	Ø22mm	80-800	59-590	708-7080	1188mm	5.6Kgs
DG®-II 11060288	Ø22mm	100-1000	74-738	885-8851	1188mm	5.6Kgs
DG®-II 11060289	Ø22mm	150-1500	110.6-1106	1328-13276	1188mm	5.6Kgs



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060205	1/2"	34-340	25-250.9	301-3010	787mm	1.65Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060203	3/8"	20-200	14.8-147	178-1780	577mm	1.3Kgs	48 teeth, 7.5 action
DG[®]-II 11060204	1/2"	20-200	14.8-147	178-1780	577mm	1.3Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060088	3/8"	10-135	7.4-99.6	89-1195	402mm	1.05Kgs	48 teeth, 7.5 action
DG[®]-II 11060095	1/2"	10-135	7.4-99.6	89-1195	402mm	1.05Kgs	48 teeth, 7.5 action

•Ø16mm Spigot Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060254	Ø16mm	34-340	25-250.9	301-3010	748mm	1.35Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060253	Ø16mm	20-200	14.8-147	178-1780	548mm	1.05Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060252	Ø16mm	10-135	7.4-99.6	89-1195	373mm	0.8Kgs

•9X12/14X18mm Female Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060258	14X18mm	34-340	25-250.9	301-3010	756mm	1.45Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060257	14X18mm	20-200	14.8-147	178-1780	545mm	1.1Kgs
DG[®]-II 11060256	9X12mm	20-200	14.8-147	178-1780	547mm	1.05Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060255	9X12mm	10-135	7.4-99.6	89-1195	370mm	0.8Kgs



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG-II 11060263	1/2"	34-340	25-250.9	301-3010	787mm	1.7Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG-II 11060261	3/8"	20-200	14.8-147	178-1780	577mm	1.35Kgs	48 teeth, 7.5 action
DG-II 11060262	1/2"	20-200	14.8-147	178-1780	577mm	1.35Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG-II 11060259	3/8"	10-135	7.4-99.6	89-1195	402mm	1.1Kgs	48 teeth, 7.5 action
DG-II 11060260	1/2"	10-135	7.4-99.6	89-1195	402mm	1.1Kgs	48 teeth, 7.5 action

•Ø16mm Spigot Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060266	Ø16mm	34-340	25-250.9	301-3010	748mm	1.4Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060265	Ø16mm	20-200	14.8-147	178-1780	548mm	1.1Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060264	Ø16mm	10-135	7.4-99.6	89-1195	373mm	0.85Kgs

•9X12/14X18mm Female Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060270	14X18mm	34-340	25-250.9	301-3010	756mm	1.5Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060269	14X18mm	20-200	14.8-147	178-1780	547mm	1.15Kgs
DG-II 11060268	9X12mm	20-200	14.8-147	178-1780	545mm	1.1Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG-II 11060267	9X12mm	10-135	7.4-99.6	89-1195	370mm	0.85Kgs



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060251	1/2"	34-340	25-250.9	301-3010	787mm	1.5Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060235	3/8"	20-200	14.8-147	178-1780	577mm	1.15Kgs	48 teeth, 7.5 action
DG[®]-II 11060236	1/2"	20-200	14.8-147	178-1780	577mm	1.15Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060233	3/8"	10-135	7.4-99.6	89-1195	402mm	0.9Kgs	48 teeth, 7.5 action
DG[®]-II 11060234	1/2"	10-135	7.4-99.6	89-1195	402mm	0.9Kgs	48 teeth, 7.5 action

•Ø16mm Spigot Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060273	Ø16mm	34-340	25-250.9	301-3010	748mm	1.2Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060272	Ø16mm	20-200	14.8-147	178-1780	548mm	0.9Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060271	Ø16mm	10-135	7.4-99.6	89-1195	373mm	0.65Kgs

•9X12/14X18mm Female Interchangeable Head



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060277	14X18mm	34-340	25-250.9	301-3010	756mm	1.3Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060276	14X18mm	20-200	14.8-147	178-1780	547mm	0.95Kgs
DG[®]-II 11060275	9X12mm	20-200	14.8-147	178-1780	545mm	0.9Kgs



	Insert Size	Nm	lbf-ft	lbf-in	Length	Weight
DG[®]-II 11060274	9X12mm	10-135	7.4-99.6	89-1195	370mm	0.65Kgs



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

SQUARE HANDLE



•Fixed Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060281	1/2"	34-340	25-250.9	301-3010	770mm	2Kgs	45 teeth, 8 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060279	3/8"	20-200	14.8-147	178-1780	570mm	1.6Kgs	45 teeth, 8 action
DG[®]-II 11060280	1/2"	20-200	14.8-147	178-1780	570mm	1.6Kgs	45 teeth, 8 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060124	3/8"	10-135	7.4-99.6	89-1198	400mm	1.2Kgs	45 teeth, 8 action
DG[®]-II 11060278	1/2"	10-135	7.4-99.6	89-1198	400mm	1.2Kgs	45 teeth, 8 action

•Flexible Head



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060284	3/8"	20-200	14.8-147	178-1780	570mm	1.6Kgs	48 teeth, 7.5 action
DG[®]-II 11060285	1/2"	20-200	14.8-147	178-1780	570mm	1.6Kgs	48 teeth, 7.5 action



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG[®]-II 11060282	3/8"	10-135	7.4-99.6	89-1198	400mm	1.05Kgs	48 teeth, 7.5 action
DG[®]-II 11060283	1/2"	10-135	7.4-99.6	89-1198	400mm	1.05Kgs	48 teeth, 7.5 action



Hearing
(Buzzer)



Vision
(LCD Screen; LED Lights)



Touch
(Vibration) *Optional



Utility
(Unit Conversions)



Memory
*Optional

3-30NM DIGITAL TORQUE WRENCH



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Teeth
DG [®] -II 11060307	1/4"	3-30	2-22	26.6-265.5	220mm	0.275Kgs	36 teeth, 10 action

3-30NM DIGITAL TORQUE WRENCH



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight	Driver
DG [®] -II 11060070	1/4"	3-30	2-22	27-266	223mm	0.43Kgs	36 teeth, 10 action

DIGITAL AD



	Driver Square	Nm	lbf-ft	lbf-in	Length	Weight
DG [®] II 11060093	1/2"	20-200	14.8-147	178-1780	75mm	0.18Kgs
DG [®] -II 11060102	3/8"	10-135	7.4-99.6	89-1195	75mm	0.18Kgs
DG [®] -II 11060337	1/4"	3-30	2-22	26.6-265.5	75mm	0.16Kgs

DIGITAL TORQUE SCREWDRIVER



	cNm	ozf-in	lbf-in	kgf-cm	Length	Weight
DG [®] -II 11060125	30-300	42.5-424.8	2.66-26.55	3.06-30.59	215mm	0.15Kgs
DG [®] -II 11060129	60-600	85-849.7	5.31-53.1	6.12-61.18	215mm	0.15Kgs