

YJ-212 Maxi Plug-in Fuse

- Voltage rating: 32 Volts
- Structure: Zinc alloy
- Test specification:

Rating	Blow Time
110%	$\geq 100\text{Hr}$
135%	$\geq 0.75\text{s}, \leq 1800\text{s}$
200%	$\geq 0.15\text{s}, \leq 5\text{s}$
350%	$\leq 0.08\text{s}$



YJ-212B20



YJ-212C1



PART NUMBERING SYSTEM

Series	Body	Marking	Packing	Rating
YJ-212	☐	☐	☐	- ☐ A
	Blank – standard PC material 2 – nylon material	Blank – standard amperage marking I – Amperage rating ink printing on the cover	Blank – 100pc in a polybag PB100 – 100pc in a plastic bag, then in a paper box B20 – 20pc in a plastic box C1 – 1pc on a blister card DB1 – 1pc on a double blister card	020 – 20 amp (Yellow) 030 – 30 amp (Green) 035 – 35 amp (Lt Red) 040 – 40 amp (Orange) 050 – 50 amp (Red) 060 – 60 amp (Blue) 070 – 70 amp (Tan) 080 – 80 amp (White) 100 – 100 amp (Violet)

YJ-213 Auto Glass Fuse

- Voltage rating: 125V
- Body: Glass tube, Flat metal: Zinc alloy
- Test specification:

Rating	Blow Time
110%	$\geq 4\text{Hr}$
135%	$\leq 1\text{Hr}$
200%	$\leq 10\text{s}$



YJ-213C10



YJ-213B5



YJ-213B100



YJ-213PB100



PART NUMBERING SYSTEM

Series	Cap	Packing	Rating		Dimensions		
YJ-107			-  A		-   V		
	Blank – metal cap D – copper cap E – external solderedcap	Blank – 100pc in a polybag B5 – 5pc in an inner box, 20 inner boxes in a paper box B100 – 100pc in a plastic box PB100 – 100pc in a paper box C10 – 10pc on a blister card	01 – 1 amp 02 – 2 amp 03 – 3 amp 04 – 4 amp 05 – 5 amp 07.5 – 7.5 amp 09 – 9 amp 10 – 10 amp 14 – 14 amp	15 – 15 amp 20 – 20 amp 25 – 25 amp 30 – 30 amp 35 – 35 amp 40 – 40 amp 50 – 50 amp	Code	available amp	Dimensions
					2AG	7.5A, 9A	1/4"X7/8"(6.35diaX22mm)
					3AG	1A to 50A	1/4"X1-1/4"(6.35diaX31.75mm)
					8AG	5A to 30A	1/4"X1"(6.35diaX25mm)
					SFE14	14A	1/4"X1-1/16"(6.35diaX27mm)
					9AG	0A, 50A	1/4"X1-7/16"(6.35diaX36mm)

YJ-214 Auto Glass Fuse



- Voltage rating: 125V/250V
- Caps: Cylindrical iron, both nickel and gold finish are available
- Body: Glass tube, Flat metal: Zinc alloy
- Dimension: 10.3diaX38mm
- Amperage rating: 0.5A to 80A
- Industry packing: 100pc/polybag, 2,000pc/18kg/20kg/1.2'
- Part number system: YJ-214- ☐ A for nickel plated cap
YJ-214G- ☐ A for gold plated cap

➤ Test specification: Rating	Amp	Blow Time
110%	35A-60A	>=4Hr
110%	0.5A-30A	>=4Hr
135%	0.5A-30Ar	<=1Hr
200%	0.5A-8A	<=5s
200%	10A-30A	<=10s
300%	35A-60A	<=4s

YJ-215 Auto Glass Fuse



- Body: Glass tube, Flat metal: Zinc alloy
- Dimension: 5.0diaX20mm
- Industry packing: 1,000pc/polybag, 20,000pc/10kg/12kg/0.82'
- Part number system: YJ-215 - ☐ A