氣動有機溶劑幫浦

AIR OPERATED DIESEL OIL PUMP

GF501 GF511

氣動有機溶劑幫浦
AIR OPERATED DIESEL OIL PUMP

特 點

(1) 本機型採用特殊油封，可抽取機油及一般有機溶劑(如：汽油、柴油、甲苯等)，但不可抽取酸鹼性溶劑(如：硫酸、鹽酸等)。
(2) 典型的使用範圍為工廠、汽修廠、船舶保養、採礦機械、農耕、軍隊、建築、大眾運輸等。
(3) 使用氣動幫浦，不須電力，可使用於有易燃物品的場所，如：加油站、汽車保養廠等場所。
(4) 幫浦本體材質採用高強度鋁合金成型。

Feature

(1) The machine uses special oil seal. It can suction engine oil and general organic solvent(example: gasoline, diesel oil, toluene), but it can't suction acidity solvent or alkaline solvent. (example: sulfuric acid, hydrochloric acid.)
(2) Typically used in workshops, service stations, fleet maintenance, mining, agriculture, armed forces, construction, trains, etc.
(3) Use pneumatic pump, no need for electric power, can be used in places with flammable substances, such as, gas station, car maintenance plant etc.
(4) The pump is made of aluminum alloy.

型號 Model	容量 Capacity	空氣輸入壓力 Air Input Pressure	壓力比 Pressure Ratio	機油輸出壓力 Oil Output Pressure	輸出量 Deliver Rate	油管長度 Hose Length	淨重 N.W.	毛重 G.W.	材積 CUFT
GF501	200L	4~9 bar 60~130 psi	1 : 1	4~9 bar 60~130 psi	150 c.c/cycle	20 ft	9.2 kgs	10.4 kgs	1.0'
GF511			5 : 1	20~45 bar 300~650 psi	140 c.c/cycle		15.7 kgs	17.2 kgs	1.2'