

Air Screwdriver



WS-301 / 301J / 301P
Two Hammer / Jumbo Hammer / Pin Less



WS-302
Two Hammer



WS-303
Two Hammer




WS-305 / 305J / 305P
Two Hammer / Jumbo Hammer / Pin Less

WS-301 Series / WS-301J Series

- 4 step torque regulator.
- The pneumatic motor with high effect designed, the high torque output of low consumption.
- 4段式扭力調節。
- 高效能氣動馬達設計，低耗氣、高扭力輸出。

WS-302 Series

- 2 steps throttle trigger of patent, it is accurate and convenient to control.
- Ergonomic designed for long time work without weary.
- Two hammer mechanism, vibration is small, suitable for Phillips screw works.
- 專利2段式板機，操控精確又便利。
- 人體工學設計，長時間作業不易疲勞。
- 雙鎚塊結構，振動小，適合十字螺絲作業。



Select the proper type of bit according to the specification of your screwdriver

Model	Std. Bolt Cap.	Hex. Drive	Torque @0.5 Sec	Torque @2 Sec	Free Speed	Air Cons. @Load	Length	Weight	Noise	Packing
型號	螺絲能力	前軸尺寸	0.5秒扭力	2秒扭力	無負載轉速	負載中耗氣量	長度	重量	噪音值	包裝明細 (CTN)
	mm	inch	Nm	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WS-301	6~8	1/4"	58	60	8,000	4.6 (130)	217	1.3	92.3	12pcs/17.5kg/18kg/0.9'
WS-301J	6~8	1/4"	57	59	8,000	4.6 (130)	217	1.3	92.3	12pcs/17.5kg/18kg/0.9'
WS-301P	6~8	1/4"	63	68	8,000	4.6 (130)	217	1.36	92.3	12pcs/18.3kg/19kg/0.9'
WS-302	6~8	1/4"	45	55	8,000	5.6 (160)	198	1	91.1	20pcs/22.5kg/23.5kg/1.4'
WS-303	6~8	1/4"	50	57	8,500	5.8 (165)	172	1.05	88.7	10pcs/12kg/13kg/0.9'
WS-305	6~8	1/4"	58	60	8,000	4.6 (130)	155	1.2	81.4	10pcs/13.4kg/14.4kg/0.83'
WS-305J	6~8	1/4"	57	59	8,000	4.6 (130)	155	1.2	81.4	10pcs/13.4kg/14.4kg/0.83'
WS-305P	6~8	1/4"	63	69	8,000	4.6 (130)	155	1.26	81.4	10pcs/14.2kg/15.2kg/0.83'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT



Two Hammer

Two Hammer mechanism, vibration is small, suitable for Phillips screw works and soft joint works.
雙鎚塊結構，振動小，適合十字螺絲起子作業、軟結合。



Jumbo Hammer

Jumbo Hammer mechanism, high torque, good durability, and low costs to maintain. (Hard joint of works)
單環鎚打結構，高扭力，耐久性佳，維護成本低，適用於硬結合。(不適合十字螺絲)

Mini Impact Wrench



WS-303 Series

- 2 steps throttle trigger of patent, it is accurate and convenient to control.
- Ergonomic designed for long time work without weary.
- Two hammer mechanism, vibration is small, suitable for Phillips screw works.
- Swivel handle exhaust.
- 專利2段式板機，操控精確又便利。
- 人體工學設計，長時間作業不易疲勞。
- 雙錘塊結構，振動小，適合十字螺絲作業。
- 排氣口可360度旋轉。

WS-305 Series

- 2 steps throttle trigger for precise control.
- Rigid hammer housing made of hot forged steel for excellent durability.
- Swivel handle exhaust.
- Comfortable contoured handle.
- 兩段式板機，可精確控制。
- 錘打組為熱鍛加工，具有特優的耐久性。
- 可旋轉式下排氣裝置。
- 具有舒適操控的把手。

Model 型號	Std. Bolt Cap. 螺絲能力	Sq. Drive Size 前軸尺寸	Torque @0.5 Sec 0.5秒扭力	Torque @2 Sec 2秒扭力	Free Speed 無負載轉速	Air Cons. @Load 負載中耗氣量	Length 長度	Weight 重量	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	inch	Nm	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WS-301W	6~8	3/8"	65	80	8,000	2.5 (70)	210	1.3	92.3	12pcs/17.5kg/18kg/0.9'
WS-301JW	8~10	3/8"	82	94	8,000	4.6 (130)	210	1.3	92.3	12pcs/17.5kg/18kg/0.9'
WS-301PW	8~10	3/8"	78	89	8,000	4.6 (130)	210	1.36	92.3	12pcs/18.3kg/19kg/0.9'
WS-302W	6~8	3/8"	55	62	8,000	5.6 (160)	190	1	91.1	20pcs/22.5kg/23.5kg/1.4'
WS-303W	6~8	3/8"	58	65	8,500	5.8 (165)	164	1.05	88.7	10pcs/12kg/13kg/0.9'
WS-305W	6~8	3/8"	80	90	8,000	4.6 (130)	155	1.2	81.4	10pcs/13.4kg/14.4kg/0.83'
WS-305JW	6~8	3/8"	82	94	8,000	4.6 (130)	155	1.2	81.4	10pcs/13.4kg/14.4kg/0.83'
WS-305PW	6~8	3/8"	79	89	8,000	4.6 (130)	155	1.26	81.4	10pcs/14.2kg/15.2kg/0.83'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT



Pin Less

Pinless mechanism, strong power on single hit with long durability. Available for both soft and hard joint of works. 無銷式結構，單次打擊能力強，耐久性佳，軟、硬結合同時共用。

Air Screwdriver

Corner Driver [90°]

2 Step throttle trigger of patent
90 angle head allows flexibility in tight spots.

專利兩段式板機。
前端90度設計，使不易維修處更彈性。



WS-304
1/4" Corner Screwdriver Two Hammer



WS-304W
3/8" Corner Impact Driver Two Hammer

Model	Std. Bolt Cap.	Drive Size	Torque @0.5 Sec	Torque @2 Sec	Free Speed	Air Cons. @Load	Length	Weight	Noise	Packing
型號	螺絲能力	前軸尺寸	0.5秒扭力	2秒扭力	無負載轉速	負載中耗氣量	長度	重量	噪音值	包裝明細 (CTN)
	mm	inch	Nm	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WS-304	6~8	1/4" Hex.	37	43	8,000	5.6 (160)	217	1.3	86.4	12pcs/17.5kg/18.3kg/0.9'
WS-304W	6~8	3/8" Sq.	52	57	8,000	5.6 (160)	217	1.3	86.4	12pcs/17.5kg/18.3kg/0.9'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

Air Screwdriver

Super Ultra Series

6 Position Power regulator : 3 settings in forward, 3 in reverse.
正、逆轉各3段位扭力調節。



WS-2052
Twin Hammer



WS-2057
Two Hammer-for soft joint of work

Model	Std. Bolt Cap.	Hex. Drive	Torque @0.5Sec	Torque @2 Sec	Free Speed	Air Cons. @Load	Length	Weight	Noise	Packing
型號	螺絲能力	前軸尺寸	0.5秒扭力	2秒扭力	無負載轉速	負載中耗氣量	長度	重量	噪音值	包裝明細 (CTN)
	mm	inch	Nm	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WS-2052	12	1/4"	190	200	12,000	5.6 (160)	145	1.6	95.4	10pcs/17kg/18kg/0.83'
WS-2057	10	1/4"	100	110	12,000	5.6 (160)	145	1.6	97.3	10pcs/17kg/18kg/0.83'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 3/8" (9.5mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

Air Screwdriver

Economy 經濟型



WX-3208
Two Hammer



WX-3218
Twin Hammer

Model 型號	Std. Bolt 螺絲能力	Hex. Drive 前軸尺寸	Max. Torque 最大扭力	Free Speed 無負載轉速	Air Cons. @Load 負載中耗氣量	Length 長度	Weight 重量	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	inch	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WX-3208	8	1/4"	55	9,000	7 (198)	155	1.18	86.5	10pcs/13.3kg/14.3kg/0.9'
WX-3218	8	1/4"	74	9,000	12 (340)	155	1.18	84.7	10pcs/12kg/14kg/0.9'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT



WX-3155S
Two Hammer



WX-3155A
Two Hammer



WX-325HP
Two Hammer



WX-318H
Two Hammer



WX-328HL
Two Hammer



WX-316LS
Two Hammer

Model 型號	Std. Bolt 螺絲能力	Hex. Drive 前軸尺寸	Max. Torque 扭力	Free Speed 無負載轉速	Air Cons. @Load 負載中耗氣量	Length 長度	Weight 重量	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	inch	Nm	RPM	cfm (l/min)	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WX-3155S	M3~M6	1/4"	47	14,000	6 (170)	187	0.78	95.3	20pcs/17.7kg/18.7kg/1'
WX-3155A	M4~M5	1/4"	25	12,000	6 (170)	193	1.1	96.6	20pcs/23.9kg/24.9kg/1'
WX-325HP	M4~M5	1/4"	46	16,000	8.8 (250)	140	0.87	95.5	10pcs/10.6kg/11.6kg/0.9'
WX-318H	M6~M8	1/4"	48	10,000	6.7 (190)	208	0.98	96.5	20pcs/24.9kg/25.9kg/1'
WX-328HL	M6~M8	1/4"	26	9,800	6.3 (180)	275	1.36	96.1	20pcs/29.3kg/30.3kg/1'
WX-316LS	M6~M8	1/4"	49	10,000	7.7 (220)	180	1.15	94.8	10pcs/15.4kg/16.4kg/1.5'

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

Shut Off Screwdriver



WX-3T-PB Series



WX-3T-LB Series



WX-3T-PBE Series

Push Start Shut off - Straight type / 直型下壓式全自動氣動起子

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	工作耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3T10PB	1,000	480	180	31	5.0	0.5-2	0.28	M1.0-M2.2	M1.1-M1.7	67	10pcs/6kg/7kg/0.58'
WX-3T20PB	1,000	480	180	31	5.0	1-8	0.28	M1.7-M3.3	M1.3-M2.7	67	10pcs/6kg/7kg/0.58'
WX-3T30PB	1,800	480	180	31	5.0	3-17	0.28	M2.2-M4.2	M1.7-M3.2	67	10pcs/6kg/7kg/0.58'
WX-3T35PB	2,200	480	180	31	5.0	3-20	0.28	M2.2-M4.5	M1.7-M3.5	67	10pcs/6kg/7kg/0.58'
WX-3T40PB	1,000	480	180	31	5.0	5-30	0.28	M2.8-M5.0	M2.2-M4.0	67	10pcs/6kg/7kg/0.58'
WX-3T45PB	8,00	480	180	31	8.0	8-40	0.28	M3.3-M5.7	M2.7-M4.4	67	10pcs/6kg/7kg/0.58'
WX-3T48PB	1,800	790	215	39	8.0	5-45	0.55	M2.8-M5.8	M2.2-M4.7	72	10pcs/10kg/11kg/0.75'
WX-3T50PB	1,400	790	215	39	8.0	7-50	0.55	M2.9-M6.0	M2.6-M4.9	72	10pcs/10kg/11kg/0.75'
WX-3T55PB	1,000	790	215	39	8.0	7-65	0.55	M2.9-M6.4	M2.6-M5.4	72	10pcs/10kg/11kg/0.75'
WX-3T60PB	550	790	215	39	8.0	15-95	0.55	M4.1-M7.0	M3.1-M6.0	72	10pcs/10kg/11kg/0.75'
WX-3T65PB	300	810	215	39	8.0	30-180	0.55	M5.0-M9.3	M4.0-M7.2	72	10pcs/10kg/11kg/0.75'
WX-3T68PB	250	810	215	39	8.0	50-280	0.55	M6.0-M11.0	M4.9-M8.7	72	10pcs/10kg/11kg/0.75'

Lever Start Shut off - Straight type / 直型壓板式全自動氣動起子

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	空氣耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3T10LB	1,000	520	205	29	5.0	0.5-2	0.2	M1.0-M2.2	M1.1-M1.7	67	10pcs/7kg/8kg/0.58'
WX-3T20LB	1,000	520	205	29	5.0	1-8	0.2	M1.7-M3.3	M1.3-M2.7	67	10pcs/7kg/8kg/0.58'
WX-3T30LB	1,800	520	205	29	5.0	3-17	0.28	M2.2-M4.2	M1.7-M3.2	67	10pcs/7kg/8kg/0.58'
WX-3T35LB	2,200	520	205	29	5.0	3-20	0.28	M2.2-M4.5	M1.7-M3.5	67	10pcs/7kg/8kg/0.58'
WX-3T40LB	1,000	520	205	29	5.0	5-30	0.28	M2.8-M5.0	M2.2-M4.0	67	10pcs/7kg/8kg/0.58'
WX-3T45LB	800	520	205	29	8.0	8-40	0.3	M3.3-M5.7	M2.7-M4.4	69	10pcs/7kg/8kg/0.58'
WX-3T48LB	1,800	820	240	37	8.0	5-45	0.55	M2.8-M5.8	M2.2-M4.7	69	10pcs/11kg/12kg/0.75'
WX-3T50LB	1,400	820	240	37	8.0	7-50	0.55	M2.9-M6.0	M2.6-M4.9	69	10pcs/11kg/12kg/0.75'
WX-3T55LB	1,000	820	240	37	8.0	7-65	0.55	M2.9-M6.4	M2.6-M5.4	69	10pcs/11kg/12kg/0.75'
WX-3T60LB	550	820	240	37	8.0	15-95	0.55	M4.1-M7.0	M3.1-M6.0	69	10pcs/11kg/12kg/0.75'
WX-3T65LB	300	840	240	37	8.0	30-180	0.55	M5.0-M9.3	M4.0-M7.2	69	10pcs/11kg/12kg/0.75'
WX-3T68LB	250	840	240	37	8.0	50-280	0.55	M6.0-M11.0	M4.9-M8.7	69	10pcs/11kg/12kg/0.75'

Push Start Shut off - Straight type (for environment protect) / 直型下壓式全自動氣動起子 (環保消音裝置)

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	空氣耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3T10PBE	1,000	480	180	29	5.0	0.5-2	0.28	M1.0-M2.2	M1.1-M1.7	67	10pcs/6kg/7kg/0.58'
WX-3T20PBE	1,000	480	180	29	5.0	1-8	0.28	M1.7-M3.3	M1.3-M2.7	67	10pcs/6kg/7kg/0.58'
WX-3T30PBE	1,800	480	180	29	5.0	3-17	0.28	M2.2-M4.2	M1.7-M3.2	67	10pcs/6kg/7kg/0.58'
WX-3T35PBE	2,200	480	180	29	5.0	3-20	0.28	M2.2-M4.5	M1.7-M3.5	67	10pcs/6kg/7kg/0.58'
WX-3T40PBE	1,000	480	180	29	5.0	5-30	0.28	M2.8-M5.0	M2.2-M4.0	67	10pcs/6kg/7kg/0.58'
WX-3T45PBE	800	480	180	29	8.0	8-40	0.28	M3.3-M5.7	M2.7-M4.4	67	10pcs/6kg/7kg/0.58'
WX-3T48PBE	1,800	790	215	37	8.0	5-45	0.55	M2.8-M5.8	M2.2-M4.7	72	10pcs/10kg/11kg/0.75'
WX-3T50PBE	1,400	790	215	37	8.0	7-50	0.55	M2.9-M6.0	M2.6-M4.9	72	10pcs/10kg/11kg/0.75'
WX-3T55PBE	1,000	790	215	37	8.0	7-65	0.55	M2.9-M6.4	M2.6-M5.4	72	10pcs/10kg/11kg/0.75'
WX-3T60PBE	550	790	215	37	8.0	15-95	0.55	M4.1-M7.0	M3.1-M6.0	72	10pcs/10kg/11kg/0.75'
WX-3T65PBE	300	810	215	37	8.0	30-180	0.55	M5.0-M9.3	M4.0-M7.2	72	10pcs/10kg/11kg/0.75'
WX-3T68PBE	250	810	215	37	8.0	50-280	0.55	M6.0-M11.0	M4.9-M8.7	72	10pcs/10kg/11kg/0.75'

● Air Pressure / 空氣壓力 : 90 Psi (6.2 bar)

● Standard Deviation / 扭力精度 : ±3 %

Shut Off Screwdriver



WX-3T-AB Series



WX-3R-PBP Series



WX-3R-BBP Series

Lever Start Shut off - Angle type / 彎頭壓板式全自動氣動起子

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	空氣耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3T20AB	1,000	660	270	29	5.0	1-8	0.28	M1.7-M3.3	M1.3-M2.7	67	10pcs/9kg/10kg/0.83'
WX-3T30AB	1,800	660	270	29	5.0	3-17	0.28	M2.2-M4.2	M1.7-M3.2	67	10pcs/9kg/10kg/0.83'
WX-3T35AB	2,200	660	270	29	5.0	3-20	0.28	M2.2-M4.5	M1.7-M3.5	67	10pcs/9kg/10kg/0.83'
WX-3T40AB	1,000	660	270	29	5.0	5-30	0.28	M2.8-M5.0	M2.2-M4.0	67	10pcs/9kg/10kg/0.83'
WX-3T45AB	800	660	270	29	8.0	8-40	0.28	M3.3-M5.7	M2.7-M4.4	67	10pcs/9kg/10kg/0.83'
WX-3T48AB	1,800	1,200	345	37	8.0	5-45	0.55	M2.8-M5.8	M2.2-M4.7	72	10pcs/14kg/15kg/0.83'
WX-3T50AB	1,400	1,200	345	37	8.0	7-50	0.55	M2.9-M6.0	M2.6-M4.9	72	10pcs/14kg/15kg/0.83'
WX-3T55AB	1,000	1,200	345	37	8.0	7-65	0.55	M2.9-M6.4	M2.6-M.4	72	10pcs/14kg/15kg/0.83'
WX-3T60AB	550	1,200	345	37	8.0	15-95	0.55	M4.1-M7.0	M3.1-M6.0	72	10pcs/14kg/15kg/0.83'
WX-3T65AB	300	1,400	345	37	8.0	30-180	0.55	M5.0-M9.3	M4.0-M7.2	72	10pcs/14kg/15kg/0.83'
WX-3T68AB	250	1,400	345	37	8.0	50-280	0.55	M6.0-M11.0	M4.9-M8.7	72	10pcs/14kg/15kg/0.83'

Push or Push-Trigger start shut off - Pistol Type / 槍型下壓按鈕式全自動氣動起子

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	空氣耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3R35PBP	2,200	950	215	31	6.35	3-20	0.55	M2.4-M4.5	M2.0-M3.5	72	10pcs/8kg/9kg/1.18'
WX-3R38PBP	1,800	950	215	31	6.35	3-25	0.55	M2.4-M4.7	M2.0-M3.8	72	10pcs/8kg/9kg/1.18'
WX-3R41PBP	1,000	950	215	31	6.35	5-35	0.55	M2.8-M5.2	M2.2-M4.2	72	10pcs/8kg/9kg/1.18'
WX-3R47PBP	550	950	215	31	6.35	10-50	0.55	M3.6-M6.0	M2.8-M4.7	72	10pcs/8kg/9kg/1.18'
WX-3R48PBP	1,800	950	215	31	9.5	7-50	0.55	M2.8-M6.0	M2.3-M4.9	72	10pcs/12kg/13kg/1.18'
WX-3R50PBP	1,400	950	215	39	9.5	10-60	0.55	M2.9-M6.2	M2.6-M5.1	72	10pcs/12kg/13kg/1.18'
WX-3R55PBP	1,000	950	215	39	9.5	12-75	0.55	M3.5-M6.6	M2.3-M5.5	72	10pcs/12kg/13kg/1.18'
WX-3R60PBP	550	950	215	39	9.5	30-110	0.55	M5.0-M7.3	M3.3-M6.2	72	10pcs/12kg/13kg/1.18'
WX-3R65PBP	300	950	215	39	9.5	30-180	0.55	M5.0-M9.3	M3.3-M7.2	72	10pcs/12kg/13kg/1.18'
WX-3R68PBP	250	1,100	215	39	9.5	50-280	0.6	M5.0-M11.0	M3.3-M8.7	78	10pcs/12kg/13kg/1.18'

Trigger Start Shut Off - Pistol Type / 槍型按鈕式全自動氣動起子

Model	Free Speed	Weight	Length	Dia	Air Hose Size	Torque Range	Air cons.	Fastening Capacity		Noise	Packing
型號	轉速	重量	長度	把手外徑	進氣管尺寸	扭力範圍	空氣耗氣量	機械螺絲	自攻螺絲	噪音值	包裝明細 (CTN)
	RPM	g	mm	mm	mm	Kgf-cm	m ³ /min	基準T	2.0T	dB (A)	PCS/N.W./G.W./CUFT
WX-3R35BBP	2,200	950	215	31	6.35	3-20	0.55	M2.4-M4.5	M2.0-M3.5	72	10pcs/8kg/9kg/1.18'
WX-3R38BBP	1,800	950	215	31	6.35	3-25	0.55	M2.4-M4.7	M2.0-M3.8	72	10pcs/8kg/9kg/1.18'
WX-3R41BBP	1,000	950	215	31	6.35	5-35	0.55	M2.8-M5.2	M2.2-M4.2	72	10pcs/8kg/9kg/1.18'
WX-3R47BBP	550	950	215	31	6.35	10-50	0.55	M3.6-M6.0	M2.8-M4.7	72	10pcs/8kg/9kg/1.18'
WX-3R48BBP	1,800	950	215	31	9.5	7-50	0.55	M2.8-M6.0	M2.3-M4.9	72	10pcs/12kg/13kg/1.18'
WX-3R50BBP	1,400	950	215	39	9.5	10-60	0.55	M2.9-M6.2	M2.6-M5.1	72	10pcs/12kg/13kg/1.18'
WX-3R55BBP	1,000	950	215	39	9.5	12-75	0.55	M3.5-M6.6	M2.3-M5.5	72	10pcs/12kg/13kg/1.18'
WX-3R60BBP	550	950	215	39	9.5	30-110	0.55	M5.0-M7.3	M3.3-M6.2	72	10pcs/12kg/13kg/1.18'
WX-3R65BBP	300	950	215	39	9.5	30-180	0.55	M5.0-M9.3	M3.3-M7.2	72	10pcs/12kg/13kg/1.18'
WX-3R68BBP	250	1,100	215	39	9.5	50-280	0.6	M5.0-M11.0	M3.3-M8.7	78	10pcs/13kg/14kg/1.18'

• Air Pressure / 空氣壓力 : 90 Psi (6.2 bar)

• Standard Deviation / 扭力精度 : ±3 %