

There is omnipotent hold fast. It's easy to clip firmly in various of thickness on process tools of plane surface. It can purge hardened surface of metal that made from discharge electricity quickly. Long life, high speed, light weight and trouble free.

專利之萬用夾頭組，可輕易地穩固夾住各種厚度的平面加工用工具，如各型油石、各型砂紙夾以及柄是平面的各式銼刀。可迅速去除因放電加工或線切割加工後，金屬表面所產生的硬化表層。壽命長、速度快、重量輕、無故障。



WX-450

**Standard Accessory**

Switch Connector  
Rat Yail File  
Triangular Taper File  
Flat Bastard File

**Option**

Half Round File

**標準配件**

轉接頭 (5mm>3mm) (No.345000390)  
圓銼刀 (No.345000321)  
三角銼刀 (No.345000322)  
平銼刀 (No.345000324)

**選配件**

半圓銼刀 (No.345000323)

Model 型號	Stroke 衝程 mm	Free Speed 衝擊速 spm	Air Cons. @Load 負載中耗氣量 cfm (l/min)	Length 長度 mm	Weight 重量 kg	Noise 噪音值 dB (A)	Packing 包裝明細 (CTN) PCS/N.W./G.W./CUFT
WX-450	5	3,400	7 (198)	800	0.52	73	10pcs/8kg/9kg/0.7'

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)



WX-451

**Standard Accessory 標準配件**

Rat Tail File 圓銼刀  
Triangular Taper File 三角銼刀  
Half Round File 半圓銼刀  
Flat Bastard File 平銼刀

Model 型號	Stroke 衝程 mm	Free Speed 衝擊速 spm	Air Cons. @Load 負載中耗氣量 cfm (l/min)	Length 長度 mm	Weight 重量 kg	Noise 噪音值 dB (A)	Packing 包裝明細 (CTN) PCS/N.W./G.W./CUFT
WX-451	10	3,700	1 (28)	180	1	85	10pcs/11 kg/12 kg/0.8'

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

• Min. Hose Size / 進氣管尺寸 : 1/4" (6.35mm)

• Air Pressure / 空氣壓力 : 90 psi (6.2bar)