

Air-Hydraulic Type

氣油壓式

- For automobile maintenance and Carriage industry, especially for produce line and repair, steel plates to be connected.
- To replace electric-welding, fast and powerful in work.
- A accurate pneumatic motor with long service life.
- Two switches design and convenient operation.

- 適合生產線與維修用，可與薄板與薄板結合聯結用，適合車箱工業與汽車維修用。
- 可取代電銲結合，強度高，施工快速。
- 氣動馬達高精度，高使用壽命。
- 雙開關設計，操作方便。



OPTION 選配件



Curve Head / 弧形拉帽頭
Design for curve surface connection
適用U型曲面

WARN 注意事項

Operating Pressure 拉桿工作氣壓值

M3 : 25 Psi

M4 : 45 Psi

M5 : 75 Psi

M6~M12 : 90~100 Psi



797009200
Regulator / 調壓閥



Standard Accessory 標準配件

1. Head / 拉帽頭 : M3*1, M4*1, M5*1, M6*1, M8*1, M10*1(on the tool), M12*1
2. Ring Nut / 拉帽頭螺帽 *7
3. Tie Rod / 拉桿: M3*2, M4*2, M5*2, M6*1, M8*1, M10*1(on the tool), M12*1
4. Stroke Regulator / 行程調節桿*1
5. Hex. Wrench / 六角板手*1
6. Spanner / 開口板手 *1
7. Regulator / 調壓閥 * 1
8. Blow Case / 吹氣盒 *1

Model 型號	Rivet Nut Capacity 拉帽能力	Stroke 行程	Max Power 最大拉力	Length 長度	Weight 重量	Air Cons 工作耗氣量	Vibrations 震動值	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	mm	kg	mm	kg	l/min	m/s ²	dB (A)	PCS/N.W./G.W./CUFT
WS-515	M3~M12	0-6.5mm	2142	310	2.5	7.5	<2.5	<80	1pc/5kg/5.7kg/1' 2pcs/9kg/10kg/2'

- Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

Pistol Type 槍型

Quick Change 快脫



Full Cage Gear Design.

全包式齒輪設計。

Model 型號	Rivet Nut Capacity 拉帽能力	Free Speed 無負載轉速	Length 長度	Weight 重量	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	RPM	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WX-516B	M3-M5	2,100	202	1.27	92.8	10pcs/13kg/15kg/0.98'
WX-517B	M6-M8	800	222	1.56	94.8	10pcs/17kg/18kg/0.98'
WX-518B	M8-M10	500	233	1.56	93.1	10pcs/17kg/18kg/0.98'
WX-519B	M10-M12	350	245	1.64	92.8	10pcs/18kg/19kg/0.98'

• Air Cons. / 工作耗氣量 : 10 cfm (285 L/min)

• Min. Hose Size / 進氣管尺寸 : 3/8" (9.5mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

• Air Pressure / 空氣壓力 : 35-90 psi

Straight 直型/Angle Type 彎型

Quick Change 快脫



WX-531B / 532B



WX-541B / 542B

Model 型號	Rivet Nut Capacity 拉帽能力	Free Speed 無負載轉速	Length 長度	Weight 重量	Noise 噪音值	Packing 包裝明細 (CTN)
	mm	RPM	mm	kg	dB (A)	PCS/N.W./G.W./CUFT
WX-531B	M5-M6	1,500	220	1.1	92.1	12pcs/18kg/19kg/1.1'
WX-532B	M8-M10	600	220	1.1	92.1	12pcs/18kg/19kg/1.1'
WX-541B	M5-M6	1,100	220 x 100	1.1	89.5	10pcs/19kg/20kg/2'
WX-542B	M8-M10	600	220 x 100	1.1	89.5	10pcs/19kg/20kg/2'

• Air Cons. / 工作耗氣量 : 4.94 cfm (140 L/min)

• Min. Hose Size / 進氣管尺寸 : 3/8" (9.5mm)

• Air Inlet / 進氣口尺寸 : 1/4" PT or NPT

• Air Pressure / 空氣壓力 : 100 psi (6.9bar)