

Air Screwdriver

AD312A

High Torque Air Screwdriver



Application



Features

- Mechanism: Pin Clutch
- Pistol type with high torque
- Suit for assembly lines of various industries

Tool Specifications • 10 Pcs/16.95 Kg /17.5 Kg/0.93'

Bolt Capacity	φ3-12
Avg/ Air Con.	2.98 CFM (84 L/min)
Air Inlet	1/4"
Air Pressure	90 PSI (6.2 Bar)
Hose Size I.D.	1/4"
Max. Torque	190 FT-LB / 257 N.m.
Free Speed	9000 RPM
Overall Length	220 mm
Net Weight	1.35 Kg (2.97 LB)

AD314A

High Torque Air Screwdriver



Application



Features

- Mechanism: Pin Clutch
- Pistol type with high torque
- Suit for assembly lines of various industries

Tool Specifications • 10 Pcs/17.45 Kg/18.0 Kg/0.93'

Bolt Capacity	φ3-14
Avg/ Air Con.	3.03 CFM (85.7 L/min)
Air Inlet	1/4"
Air Pressure	90 PSI (6.2 Bar)
Hose Size I.D.	1/4"
Max. Torque	220 FT-LB / 298 N.m.
Free Speed	9500 RPM
Overall Length	220 mm
Net Weight	1.40 Kg (3.10 LB)

AD206A

High Speed Air Screwdriver



Application



Features

- Suit for light work, maintaining and assembling application
- Small size, light weight, small vibration.
- Simple start lever, light weight & save effort.
- Forward & Reverse switching structure.
- Adjustable clutch device provides torque control.
- High speed stepless automatic transmission.

Tool Specifications • 25 Pcs/21.5 Kg/22.1 Kg/1.0'

Bolt Capacity	φ2-5
Avg/ Air Con.	2.3 CFM (63 L/min)
Air Inlet	1/4"
Air Pressure	90 PSI (6.2 Bar)
Hose Size I.D.	1/4"
Max. Torque	33 FT-LB / 45 N.m.
Free Speed	9000 RPM
Overall Length	6-1/2" (165 mm)
Net Weight	0.69 Kg (1.52 LB)

AD409A

High Speed Air Screwdriver



Application



Features

- High speed, powerful, suit for assembly lines of various industries.
- Small vibration.
- Simple start lever, light weight & save effort.
- Forward & Reverse switching structure.
- Adjustable clutch device provides torque control.
- High speed stepless automatic transmission.

Tool Specifications • 25 Pcs/30.0 Kg/30.6 Kg/1.0'

Bolt Capacity	φ4-8
Avg/ Air Con.	3.0 CFM (82 L/min)
Air Inlet	1/4"
Air Pressure	90 PSI (6.2 Bar)
Hose Size I.D.	1/4"
Max. Torque	60 FT-LB / 80 N.m.
Free Speed	8000 RPM
Overall Length	220 mm
Net Weight	1.10 Kg (2.43 LB)

Auto Shut-off Air Screwdriver



AD203BSS2 Air Screw Driver (2.6-3.0mm)

▲ Tool Specifications

Air inlet	1/8"
Max. free speed	1,000 RPM
Air pressure	90 PSI (6.2 BAR)
Air hose size	3/8"
Avg/ Air Con.	5 CFM
Torque range	0.2-0.7 N.m
Weight	0.34 Kgs
Length	205mm



AD304BSS2 Air Screw Driver (3.0-4.0mm)

▲ Tool Specifications

Air inlet	1/4"
Max. free speed	1,700 RPM
Air pressure	90 PSI (6.2 BAR)
Air hose size	3/8"
Avg/ Air Con.	5 CFM
Torque range	0.7-1.5 N.m
Weight	0.56 Kgs
Length	215mm



AD405BSS2 Air Screw Driver (4.0-5.0mm)

▲ Tool Specifications

Air inlet	1/4"
Max. free speed	1,100 RPM
Air pressure	90 PSI (6.2 BAR)
Air hose size	3/8"
Avg/ Air Con.	5 CFM
Torque range	1.6-2.5 N.m
Weight	0.75 Kgs
Length	235mm