



**TR-5502/TR-5503**  
1/4", 3/8" Air Ratchet Wrench (20 Ft-Lb)



**TR-5536/TR-5536A**  
1/4", 3/8" Mini Air Ratchet Wrench (30 Ft-Lb)



**TR-5055(A)**  
1/4", 3/8" Mini Air Ratchet Wrench (30 Ft-Lb)



**TR-5052/TR-5053**  
3/8", 1/2" Air Ratchet Wrench (50 Ft-Lb)



**TR-5054**  
1/2" H/D Air Ratchet Wrench (90 Ft-Lb)



**TR-5056/TR-5057**  
1/2", 3/8" H/D Air Ratchet Wrench (Two Gear) (50 Ft-Lb)



**TR-5506/TR-5507**  
3/8", 1/2" H/D Air Ratchet Wrench (Two Gear) (60 Ft-Lb)



**TR-5058/TR-5058A**  
3/8", 1/2" H/D Air Ratchet Wrench (75 Ft-Lb)



**TR-5556/TR-5557**  
3/8", 1/2" H/D Air Ratchet Wrench (50 Ft-Lb)

**Specification** (at 90 PSI)

Model No.	Square Drive	Capacity (Bolt Size)		Free Speed (Rpm)	Max. Torque		Overall Length		Air Inlet (Pt/Npt)	Air Hose (I.D.)	Avg. Air Consumption		Net Weight	
		inch	mm		Ft-Lb	N-M	inch	mm			Cfm	L/Min.	Kgs	Lbs
TR-5052(3)	3/8"(1/2")	3/8"	M10	160	50	68	10"	254	1/4"	3/8"	4	113	1.1	2.4
TR-5054	1/2"	1/2"	M13	150	90	122	14-3/8"	365	1/4"	3/8"	6	170	2.0	4.4
TR-5055(A)	1/4"(3/8")	5/16"	M8	230	30	40	6-1/2"	165	1/4"	5/16"	4	113	0.5	1.1
TR-5056(7)	3/8"(1/2")	1/2"	M13	170	50	68	10-1/2"	227	1/4"	3/8"	5	142	1.17	2.57
TR-5058(A)	3/8"(1/2")	1/2"	M13	160	75	100	9"	230	1/4"	3/8"	7	198	1.2	2.64
TR-5502(3)	1/4"(3/8")	1/4"	M6	420	20	28	4-7/10"	125	1/4"	1/4"	3	85	0.4	0.88
TR-5506(7)	3/8"(1/2")	1/2"	M13	180	60	81	10-9/10"	276	1/4"	3/8"	4	113	1.2	2.6
TR-5536(A)	3/8"(1/2")	1/3"	M8	250	30	40	7-3/4"	197	1/4"	1/4"	3	85	0.62	1.37
TR-5556(7)	3/8"(1/2")	1/3"	M10	160	50	68	10"	254	1/4"	1/4"	4	113	1.1	2.4



**TR-5500/TR-5501**  
1/4", 3/8" Composite Mini Air Ratchet Wrench (16 FT-Lb)



**TR-5513**  
3/8" Composite Mini Air Ratchet Wrench (20 FT-Lb)



**TR-5527/TR-5527A**  
1/4", 3/8" Composite Mini Air Ratchet Wrench (20 FT-Lb)



**TR-5528/TR-5528A**  
3/8", 1/2" Composite Mini Air Ratchet Wrench (80 FT-LB)



**TR-5514/TR-5508**  
3/8", 1/2" Composite Mini Air Ratchet Wrench (50 FT-LB)



**TR-5529/TR-5529A**  
3/8", 1/2" Composite Air Ratchet Wrench (100 FT-LB)



**TR-5509/TR-5510**  
3/8", 1/2" Composite Air Ratchet Wrench (60 FT-LB)



**TR-5519/TR-5520**  
3/8", 1/2" Composite Air Ratchet Wrench (80 FT-LB)



**TR-5515/TR-5516**  
3/8", 1/2" Composite Air Ratchet Wrench (100 FT-LB)

## Specification (at 90 PSI)

Model No.	Square Drive	Capacity (Bolt Size)		Free Speed (Rpm)	Max. Torque		Overall Length		Air Inlet (Pt/Npt)	Air Hose (I.D.)	Avg. Air Consumption		Net Weight	
		inch	mm		Ft-Lb	N-M	inch	mm			Cfm	L/Min.	Kgs	Lbs
TR-5500(1)	1/4"(3/8")	1/4"	M6	350	16	22	5-1/2"	139	1/4"	1/4"	4	113	0.5	1.1
TR-5508/TR-5514	1/2"(3/8")	5/16"	M8	270	50	68	8-1/16"	205	1/4"	3/8"	3	85	0.66	1.45
TR-5509(10)	3/8"(1/2")	1/2"	M13	160	60	81	8-1/2"	216	1/4"	3/8"	4	113	1.2	2.6
TR-5513	3/8"	1/4"	M6	250	20	27	8-1/16"	205	1/4"	5/16"	2.8	79	0.66	1.45
TR-5515(6)	3/8"(1/2")	1/2"	M13	225	100	135	12-1/3"	315	1/4"	3/8"	4	113	1.62	3.56
TR-5519(20)	3/8"(1/2")	3/8"	M10	280	80	108	11"	277	1/4"	3/8"	4	113	1.24	2.7
TR-5527(A)	1/4"(3/8")	1/4"	M6	250	20	27	8-1/10"	205	1/4"	1/4"	2.8	49	0.66	1.46
TR-5528(A)	3/8"(1/2")	1/2"	M13	280	80	108	10-1/5"	260	1/4"	3/8"	4	113	1.24	2.93
TR-5529(A)	3/8"(1/2")	1/2"	M14	225	100	136	12-1/10"	307	1/4"	3/8"	4	113	1.52	3.35