


Fitting




Double Stud Fitting
SF202P-062018025

B.S: 2300kg
Finish: Zinc




Double Stud Fitting with O ring
SF202-062018025TZ-O

B.S: 2300kg
Finish: Zinc




End Fitting
EF101-051YY

B.S: 2300kg
Finish: Yellow Zinc




Forged End Fitting
EF103-02540127061Y

B.S: 2300kg
Finish: Yellow Zinc



Single Stud Fitting
SF102P-0286050

B.S: 1300kg
Finish: Anodized



Safety Buckle



Harness Safety Buckle
Supplied with various material on the body, bolt and buckle, hooks
for varying harness configurations.



Harness Safety Buckle
HSB-001AL-GG

Min. Breaking Strength: 12kN/2500lbs
Aluminum Alloy
Safety Locking System
Webbing: 1 3/4" (45mm)
Net Weight: 75g




Harness Safety Buckle
HSB-001H1

Min. Breaking Strength: 15kN/3000lbs
Alloy Steel
Safety Locking System
Webbing: 1 3/4" (45mm)
Net Weight: 120g



Harness Safety Buckle
HSB-001SP-1

Min. Breaking Strength: 10kN/2000lbs
SUS 304/SUS 316
Safety Locking System
Webbing: 1 3/4" (45mm)
Net Weight: 149 gm



Swivel Connector



Swivel Connector
SWC-01

Min. Breaking Strength: 40kN/8900lbs
Forged Alloy Steel



Stainless Swivel Connector
SWC-02

Min. Breaking Strength: 35kN/7500lbs
SUS 304/SUS 316



Aluminum Swivel Connector
SWC-03

Min. Breaking Strength: 9kN/2000lbs
Forged Aluminum Alloy
Anodized Silver




Aluminum Swivel Connector
SWC-04

Min. Breaking Strength: 9kN/2000lbs
Forged Aluminum Alloy
Anodized Gold



Aluminum Swivel Connector
SWC-05

Min. Breaking Strength: 9kN/2000lbs
Forged Aluminum Alloy
Anodized Pink



Item No.	A mm	B mm	C mm	D mm
SWC-01/02	43	27	43.5	127
SWC-03/04/05	29.4	17	19.5	69.4