

Industrial Tools



P01



P12



P21



P27



P30



P32



P33



P35



P37



P41



P47

HONG BING PNEUMATIC INDUSTRY CO., LTD.



Established in Shan-Kang Dist., Taichung City in 1974, originally named "Hong-Bing Iron Works Company", focus on OEM for hand tool accessory. Start manufacturing air tool in 1979. Hong Bing Pneumatic Industry Co., Ltd was founded in 1987 as professional air tools manufacture factory.

HONG BING has been approved by ISO 9001(SGS) and CE (TUV). HONG BING has gathered many years experience of R&D and Q.C., while engaging in innovative and stabilizing quality. On production facility, we use automatic and semi-automatic CNC, and strictly manufacturing key spare parts. It will increase the good rate and accurate.

HONG BING is your best choice for industrial applications of pneumatic tools.

1974年始創於台中市神岡區，原名「宏斌鐵工廠」初期專精於手工具零件代工製造。1979年投入氣動工具製造，於1987年創立「宏斌氣動工業股份有限公司」專業生產氣動工具。

宏斌已通過 ISO 9001(SGS)、CE (TÜV) 認證。在研發設計與品管作業，累積多年來的經驗，積極創新產品與穩定產品品質。在生產設備方面，採用全自動與半自動化設備加工，嚴格製造關鍵性零組件，有效提升產品良率及精準度。

宏斌對於氣動力學的工具與工業設備都會是您在工業應用領域中最佳的選擇。

CONVERSION CHART / 單位換算表

• LENGTH / 長度

1in=0.02554 m
1ft=12 in

1 m = $\begin{cases} 39.3701 \text{ in} \\ 3.28084 \text{ ft} \end{cases}$

• WEIGHT / 重量

1lb=0.453592 kg
1kg=2.20462 ft

• TORQUE / 扭力

1kgm=9.80665 Nm
1lbf=1.35582 Nm
1ft-lbs=0.138 kg-m

1Nm = $\begin{cases} 0.101972 \text{ kgm} \\ 0.7375562 \text{ lbf x ft} \end{cases}$

• PRESSURE / 壓力

1bar=100 kPa
1kg/cm²(at)=98.0665 kPa
1psi=6.89476 kPa

1kPa = $\begin{cases} 0.01\text{bar} \\ 0.0101972 \text{ kg/cm}^2 \text{ (at)} \\ 0.145038 \text{ psi} \end{cases}$

• POWER / 功率

1kpm/s=9.80665 w
1kcal/s=4.1868 kw
1kcal/h=1.163 w
1hk=735.499 w
1hp=745.7 w

1kw = $\begin{cases} 101.972 \text{ kpm/cm}^2 \text{ (at)} \\ 0.238846 \text{ kcal/s} \\ 859.845 \text{ kcal/h} \\ 1.35962 \text{ hk} \\ 1.34102 \text{ hp} \end{cases}$


• FLOW / 流率

1m³/min=16.6667 L/s=35.335 cfm
1cfm=0.471947 L/s=0.0283 m³/min 1L/s=201189cfm
1m³/min=0.277778 L/s

Air Screwdriver and Air Wrench Selection Guide

氣動螺絲起子與
氣動扳手選用建議


ANGLE 彎頭型



STRAIGHT 直柄型



PISTOL 手槍型



IMPACT SCREWDRIVER 衝擊型螺絲起子

MODEL 型 號					301L90	301A1	311LHA	100A1
					320	301AH	310LHA	308DA1
					403LN	808A1	306	310DA
						301LA1	310Q	330DQ
						601A	328Q	100LA1
							809A1	310LDA
							306SL	409WA1
							310LQ	605DA
							328LQ	606DQ
							406LN	906DAQ

CLUTCH TYPE SCREWDRIVER 離合型螺絲起子

MODEL 型 號					103	302L90	103G	
					304A1	302	301LCG	
					304B1	5C1419	2C8425	
					314A1	5C1515		
					5C1218	405LN		
					301LC	5C5415		
					404LN			

TORQUE CONTROL SCREWDRIVER 扭力控制型螺絲起子

MODEL 型 號	106A	106B		2S2110	5SLA15	5SLA08	5SLA03	
	1S0625	1S0607		5S1515C	2S3215	5S5108A	2S4304	
				5S5115C	5S1508B	5S1508A	5S5103	
					5S1515B	2S3208		
					5S5108B	2S4307		
					5S5115B			
SCREW SIZE 螺絲尺寸	2mm	2.5mm	3mm	3.5mm	4mm	5mm	6mm	8mm

IMPACT WRENCH 衝擊型扳手

MODEL 型 號	301LB90	301B3	311LH3	308DW	100B	130LH4	130B	603D	936D2	912D2	913D2	914D2
		301LB3	310LH3	310DB4		100LB	131LB	908D			915DA	
		403LB3	306B	330D4		906D4		909D				
			310B3	310LD4		606D4						
			328B3	409WHA								
			809B1	310LB3								
			306SL1	328LB3								
				406LB								
				605D4								
BOLT SIZE 螺栓尺寸	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30
NUT SIZE 螺帽尺寸	10mm	13mm	17mm	19mm	22mm	24mm	27mm	30mm	32mm	36mm	41mm	46mm

Needle Scaler

除銹器



OP-120



OP-16



OP-100-2B



OP-J288

SPECIFICATION(air pressure at 90psi、6.2bar、6.3kg/cm²)

MODEL 型號	Blows Per Min 衝擊數 (B.P.M.)	Needle Diameter 鋼針直徑 mm	Number of Needles 鋼針數 pcs	Piston Diameter 活塞直徑 mm	Piston Stroke 活塞行程 mm	inch	Air Consumption 耗氣量 l/min	cfm	Overall Length 全長 mm	inch	Air Inlet 入氣接頭 PT	Net Weight 重量 kg	lb
OP-120	2500	ø4x180	35	ø33x94	52	2	210	7.4	460	18.11	1/4	6	13.2
OP-16	4000	ø2x150	29	ø16x59	36	1.4	71	2.5	285	11.22	3/8	1.6	3.5
OP-100-2B	3700	ø3x180	19	ø23.5x70	38	1.5	85	3	375	14.76	1/4	2.8	6.2
OP-J288	5500	ø3x125	12	ø18x47	28	1.1	283	10	290	11.41	1/4	1.19	2.62



OP-CM-50

OP-CM-50

Air caulking gun
氣動膠槍

- Plastic gun size :215~240mm
- Air pressure : 3kg/cm² (45 psi)
- Length : 280 mm
- Weight : 0.53 kg
- 使用膠管尺寸 : 215~240mm
- 最高空氣壓力 : 3kg/cm² (45 psi)
- 長度 : 280mm
- 重量 : 0.53kg



OP-S105
Air body saw
氣動鋸




OP-CP1223
Air engraving pen
氣動雕刻筆



OP-288N
Air flux chipper
氣動雕刻刀

Chisel Shank



SPECIFICATION(air pressure at 90psi、6.2bar、6.3kg/cm²)

MODEL 型號	Cutting Capacity Thickness 剪切厚度能力 Aluminum(mm)	Blows Per Minute 衝擊數 B.P.M	Air Consumption 耗氣量 l/min	cfm	Overall Length 全長 mm	inch	Air Inlet 入氣接頭 PT	Net Weight 重量 kg	lb
OP-S105	3.0	9000	127	4.5	235	9.25	1/4	0.6	1.32
OP-CP1223		2300	28	1	170	6.69	1/4	0.23	0.5
OP-288N		4800	283	10	235	9.25	1/4	1.21	2.67